





XCell Sensors

MSA XCell Sensors are a breakthrough in sensor design, enabling faster response and shorter span calibrations, saving you time and money. ASIC (application-specific integrated circuit) technology inside of each sensor provides greater control and higher performance than other sensors on the market.

Every XCell Sensor is built by MSA with a proprietary embedded ASIC microchip that drives the sensor and converts its output to a digital signal. This microchip is much more than a digital sensor; XCell Sensors perform real-time environmental corrections, provide plug-and-play capabilities and deliver greater RF immunity with higher overall performance.

MSA XCell Sensors have a typical life of more than four years*, double the industry average. By miniaturizing sensor controlling electronics and placing them inside of the sensor itself, MSA XCell Sensors offer superior response time, stability, accuracy, and reliability. MSA is proud to offer XCell Sensors with:

- State-of-the-art automated assembly for greater control and reliability.
- Laser-welded sensor housings to eliminate opportunities for leaks.
- End-of-sensor-life warning to minimize downtime and inventory replacement.

With less time spent on calibration and bump tests, you save on calibration gas, maintenance costs and in turn, save money. But most importantly, MSA's industry-leading response times help to save lives.



^{*}Refers to most standard XCell Sensors. Specific exotic gas and special application sensors have shorter expected lives. Please refer to www.MSAsafety.com for additional information.



Combustible

Ex Sensor P/N 10106722 ALTAIR 4XR, ALTAIR 5X

Gas: Combustible (LEL) **Package:** Single gas

Range:0-100% LEL or 0-5% CH4Resolution:1% LEL or 0.05% Vol CH4Response Time (typ):t(90) < 10 seconds (methane)t(90) < 15 seconds (pentane)Alarm Setpoint:Min 5% LEL/ Max 60% LEL

Warranty: 3 years

Advantages: • Long life: >4-year life using dual detector beads means fewer sensor replacements over the instrument's life.

- $\bullet \ \, \text{Durable: patented support system allows sensor to survive a 6-meter drop in an ALTAIR}^{\bullet} \ 4X \ Multigas \ Detector.$
- Response: industry-leading response time not only helps to save lives, but your time and money as well.
- Performance: run up to 3 shifts with XCell Sensor's low power consumption.
- Resilience: extremely robust filter helps to keep sensors free of poisons and inhibitors.

Ex-M Sensor P/N 10121212 ALTAIR 4XR

Gas: Combustible (LEL) **Package:** Single gas

 $\begin{array}{lll} \textbf{Range:} & 0\text{-}100\% \text{ LEL or } 0\text{-}5\% \text{ CH}_4 \\ \textbf{Resolution:} & 1\% \text{ LEL or } 0.05\% \text{ Vol CH}_4 \\ \textbf{Response Time (typ):} & t(90) < 10 \text{ seconds (methane)} \\ \textbf{Alarm Setpoint:} & \text{Min } 2\% \text{ LEL/ Max } 60\% \text{ LEL} \\ \text{Min } 0.1\% \text{ VOL/ Max } 3\% \text{ VOL} \\ \end{array}$

Warranty: 3 years

Advantages: • Specialized: additional stability for extended CH₄ exposures found in

mining/liquefied natural gas (LNG) applications.

· Long life: >4-year life using dual detector beads means fewer sensor replacements over the instrument's life.

• Resilience: extremely robust filter helps to keep sensors free of poisons and inhibitors.



ALTAIR 4X, ALTAIR 4XR, ALTAIR 5X

GasCombustible (LEL)Package:Single gas

Range:0-100% LEL or 0-5% CH4Resolution:1% LEL or 0.05% Vol CH4Response Time (typ):t(90) < 10 seconds (methane)t(90) < 15 seconds (pentane)Alarm Setpoint:Min 5% LEL/ Max 60% LEL

Warranty: 1 year

Advantages: • Specialized: increased response to select solvents and heavy hydrocarbons

(acetone, nonane, methyl ether keytone [MEK], xylene).



Oxygen

O₂ Sensor P/N 10106729

ALTAIR 4X, ALTAIR 4XR, ALTAIR 5X

ALTAIR 4X, ALTAIR 4XR, ALTAIR 5X

Gas: Oxygen Package: Single gas Range: 0-30% Vol O₂ **Resolution:** $0.1\% O_{2}$

Response Time (typ): t(90) < 10 seconds Min 5% Vol/ Max 24% Vol **Alarm Setpoint:**

Warranty: 3 years

• Long life: >4-year life, more than 100% additional life than Advantages:

other lead-based sensors.

• False-alarm rejection: don't be fooled; XCell Sensors are immune to pressure spikes. • Durable: when other sensors freeze, XCell Sensors keep working down to -40°C.



Carbon Monoxide

CO/H₂S Sensor

Gas: Carbon monoxide

Package: Two-tox 0-1999 ppm CO Range: Resolution: 1 ppm CO Response Time (typ): t(90) <15 seconds

Min 10 ppm/ Max 1700 ppm **Alarm Setpoint:**

Warranty:

• Long life: >4-year life means fewer sensor replacements over Advantages:

the instrument's life.

P/N 10106725

• Reliability: virtually no cross-channel interference brings accuracy to a new level.

• Stability: when it comes to helping to savings lives, be secure in knowing that XCell Sensors

are rock solid performers.

• Response: industry-leading response time not only helps to save lives, but your time and money as well.

• Resilience: extremely robust filter means that you see the gas of interest.





CO-HC Sensor P/N 10121216 ALTAIR 5X

Gas: Carbon monoxide (high concentration)

Package:Single gasRange:0-10,000 ppm COResolution:5 ppm CO

Response Time: t(90) < 15 seconds normal temperature

Alarm Setpoint: Min 10 ppm/ Max 8500 ppm

Warranty: 3 years

Advantages: • Performance: extended range for high concentration

CO applications.

- Long life: >4-year life means fewer sensor replacements over the instrument's life.
- Reliability: feel confident that XCell Sensor's linearity provides accuracy across the entire readable range.
- Response: industry-leading response time not only helps to save lives, but your time and money as well.
- Resilience: extremely robust filter means that you can even operate within environments where alcohol

vapors may be present.

H₂S/CO H₂ RES Sensor P/N 10121214

ALTAIR 4X, ALTAIR 4XR, ALTAIR 5X

Gas: Carbon monoxide (hydrogen-resistant)

Package:Two-toxRange:0-1999 ppm COResolution:1 ppm CO

Response Time: t(90) < 15 seconds normal temperature

Alarm Setpoint: Min 10 ppm/ Max 1700 ppm

Warranty: 3 years

Advantages: • Performance: this XCell Sensor has a very low cross-sensitivity

to Hydrogen <5%.

- Long life: >4-year life means fewer sensor replacements over the instrument's life.
- Response: industry-leading response time not only helps to save lives, but your time and money as well.
- Resilience: extremely robust filter means that you see the gas of interest.



Hydrogen Sulfide

CO/H₂S Sensor P/N 10106725

ALTAIR 4X, ALTAIR 4XR, ALTAIR 5X

Gas:Hydrogen sulfidePackage:Two-toxRange:0-200 ppm H2SResolution:1 ppm H2SResponse Time (typ):t(90) <15 seconds</th>

Alarm Setpoint: Min 5 ppm/ Max 175 ppm

Warranty: 3 years

Advantages: • Long life: >4-year life means fewer sensor replacements over the

instrument's life.

• Response: industr y-leading response time not only helps to save lives, but your time and money as well.

• Stability: when it comes to helping to save lives, be secure in knowing that XCell Sensors are rock solid performers.

CO/H₂S-LC Sensor P/N 10121213

ALTAIR 4X, ALTAIR 4XR, ALTAIR 5X

Gas: Hydrogen sulfide (low concentration)

Package:Two-toxRange: $0-100 \text{ ppm H}_2\text{S}$ Resolution: $0.1 \text{ ppm H}_2\text{S}$ Response Time (typ):t(90) < 15 secondsAlarm Setpoint:Min 1 ppm/ Max 70 ppm

Warranty: 3 years

Advantages: Long life: >4-year life means fewer sensor replacements over the instrument's life.

• False -alarm rejection: don't be fooled; increased sensitivity means fewer false alarms, allowing you to work

uninterrupted.

• Response: industry-leading response time not only helps to save lives, but your time and money as well.






Sulfur Dioxide

SO₂ Sensor P/N 10106727 **ALTAIR 5X**

Gas: Sulfur dioxide Package: Single gas Range: 0-20 ppm SO₂ Resolution: 0.1 ppm SO₂ Response Time (typ): t(90) < 10 seconds **Alarm Setpoint:** Min 0.5 ppm/ Max 17.5 ppm

Warranty: 3 years

• Long life: >4-year life outlasts competition by more than 33%. Advantages:



• Resilience: XCell Sensors continues to perform within low humidity environments when others do not.



ALTAIR 4X, ALTAIR 4XR

Gas: Sulfur dioxide Package: Two-tox 0-20 ppm SO₂ Range: Resolution: 0.1 ppm SO₂ Response Time (typ): t(90) <15 seconds **Alarm Setpoint:** Min 1 ppm/ Max 17.5 ppm

Warranty: 3 years

• Long life: >4-year life outlasts competition by more than 33%. Advantages:

• Response: industry-leading response time not only helps to save lives, but your time and money as well. • Resilience: XCell Sensors continues to perform within low humidity environments when others do not.



Nitrogen Dioxide

CO/NO₂ Sensor P/N 10121217

ALTAIR 4X, ALTAIR 4XR, ALTAIR 5X

Gas: Nitrogen dioxide **Package:** Two-tox

Range: $0-50 \text{ ppm NO}_2$ Resolution: 0.1 ppm NO_2 Response Time (typ):t(90) < 15 secondsAlarm Setpoint:Min 1 ppm/ Max 47.5 ppm

Warranty: 3 years

Advantages: • Long life: >4-year life means fewer sensor replacements over the instrument's life.

• Response: industry-leading response time not only helps to save lives, but your time and money as well.

• Stability: when it comes to helping to save lives, be secure in knowing that XCell Sensors are rock solid performers.



NH₃ Sensor P/N 10106726 ALTAIR 5X

Gas:AmmoniaPackage:Single gasRange:0-100 ppm NH3Resolution:1 ppm NH3Response Time (typ):t(90) <40 seconds</th>Alarm Setpoint:Min 10 ppm/ Max 75 ppm

Warranty: 2 years

Advantages: • Long life: >3-year life with patent-pending non-consuming reaction outlasts

competition by more than 50%.

• Resilience: XCell NH₃ Sensors recover from repeated exposures, meaning fewer sensor replacements.

• Response: industry-leading response time not only helps to save lives, but your time and money as well.



Not suitable for continuous NH₃ exposure.



Chlorine

Cl₂ Sensor P/N 10106728 ALTAIR 5X

Gas:ChlorinePackage:Single gasRange:0-10 ppm Cl2Resolution:0.05 ppm Cl2Response Time (typ):t(90) <30 seconds</th>Alarm Setpoint:Min 0.3 ppm/ Max 7.5 ppm

Warranty: 2 years

Advantages: • Life: >3-year life, patent-pending non-consuming reaction outlasts

competition by more than 50%.

• Response: industry-leading response time not only helps to save lives, but your time and money as well.

• Stability: when it comes to helping to save lives, be secure in knowing that XCell Sensors are rock solid performers.

• Resilience: XCell Sensors continue to perform within low humidity environments when others do not.



XCell Sensor Applications

	Combustible			Oxygen Carbon Monoxide				Hydrogen Sulfide		Sulfur Dioxide		Nitrogen Dioxide	Ammonia	Chlorine
	Ex	Ex-M	Ех-Н	0,	CO/H ₂ S	СО-НС	H₂S/CO H₂ RES	CO/H ₂ S	CO/ H₂S-LC	SO ₂	H ₂ S-LC/ SO ₂	CO/NO ₂	NH ₃	Cl ₂
AEROSPACE														
AGRICULTURE								-						
AUTOMOTIVE														
AVIATION														
CHEMICAL														-
FIRE														
FOOD/BEVERAGE								•				-	-	-
FOUNDRIES														
HAZMAT														
HEAVY MANUFACTURING														
HVAC														
INDOOR AIR QUALITY														
MARINE														-
MEDICAL														
MINING														
OIL/GAS/PETROLEUM														
PAPER/PULP														
PHARMACEUTICAL														
POWER														
SEMICONDUCTOR														
STEEL														
WATER/WASTEWATER														
WELDING														

^{*}Additional sensors available for detection of PH_3 , HCN, CIO_2 , NO, and CO_2 in the ALTAIR 5X Multigas Detector

XCell Sensor Instrument Compatibility

	Ex	Ex-M	Ex-H	02	CO/H₂S	со-нс	H₂S/CO H₂ RES	CO/ H₂S-LC	SO ₂	H ₂ S-LC/ SO ₂	CO/NO ₂	NH₃	Cl ₂
ALTAIR 4XR/ ALTAIR 4X	YES	YES	YES	YES	YES	NO	YES	YES†	NO	YES†	YES†	NO	NO
ALTAIR 5X	YES	NO	YES	YES	YES	YES‡	YES	YES‡	YES	NO	YES‡	YES	YES

[†] Requires ALTAIR 4X Multigas Detector software version 2.03 or greater

[‡] Requires ALTAIR 5X Multigas Detector software version 1.27.06 or greater





MSA-The Safety Company

Established in 1914, MSA Safety Incorporated is the global leader in the development, manufacture and supply of safety products that protect people and facility infrastructures. Many MSA products integrate a combination of electronics, mechanical systems and advanced materials to protect users against hazardous or life-threatening situations. The company's comprehensive product line is used by workers around the world in a broad range of markets, including the oil, gas and petrochemical industry, the fire service, the construction industry, mining and the military. MSA's core products include self-contained breathing apparatus, fixed gas and flame detection systems, portable gas detection instruments, industrial head protection products, fire and rescue helmets, and fall protection devices.

Trust & Durability

For nearly 100 years our passionate mission of safety empowers us, "The Safety Company", to protect lives. We are committed to providing the latest in innovative, best-in-class safety solutions that feature integrated systems capability and allow our customers to return safely to their families and friends.

Every day our customers place their lives in our hands. In response, we provide them with protection they can trust, and their stories become our stories. Hand in hand, we partner with our customers to earn that trust.

MSA: We Know what's at stake.